9-in-1 USB4 Docking Station

DUF-901

Key Features

- Enhance your at-home workforce with a USB docking station to take the multi-tasking capability of your workstation to a new level
- The Power Button switches on and off all the ports at once
- High-quality display outputs for presentation and entertainment – multi-functional USB Type-C and DP 1.4 ports support screen extension or mirroring with dual display
- Connect a diverse array of devices with the multi-functional USB4, for example, 8K monitors for the ultimate high-quality visuals[2]
- The high-speed data transfer of 40 Gbps[1] of the USB4 port supports a wide range of accessories, including external storage and recording devices
- Charge your laptop with up to 100W directly through the USB Type-C port with PD 3.0
- The aluminium alloy case combined with the ventilation holes for effective heat dissipation makes it lightweight and cooler
- The 2.5GbE provides higher speeds than GbE, bringing smoother performance





User Benefits

Maximised Work Productivity

The all-in-one connectivity answers your demand for any kind of connectivity through a single USB Type-C connection

Clutter-free Desk

The consolidated connectivity eases data accessibility and reduces cable clutter, creating a tidier workspace

Time Efficiency

The high-bandwidth capability of USB4 improves efficiency in large file transfers, 4k/8K video editing, and gaming

Streamlined Workflow

The variety of the connectors makew it ideal for any workload and optimal for multitasking in video editing or media streaming

Superior Multimedia Experience

Multiple displays provide immersive experience with 8K true-to-life visuals during content creation and gameplay

Space Efficiency

Its compact and lightweight design allows it to fit into any space-constrained area and be relocated when necessary

Instant Network

Laptops without an Ethernet port can gain high-speed connectivity with the 2.5GbE port, ensuring immediate access to fast, reliable networking for your applications

Best Work-at-home Partner

This powerhouse device streamlines all your connectivity needs for business and personal uses, no matter your profession and work style

Technical Specifications

General	
Device Interfaces[1]	**Video Ports:** • 2 x DP 1.4 (7680x4320@30Hz) • 1 x USB Type-C 4.0 with DP 1.4 Alt Mode (multi-functional connector) **Network Port:** • 1 x RJ45 (2.5 Gbps) **USB Ports:** • 1x USB Type-C 4.0: 40 Gbps with 7.5W (5V@1.5A) power output (multi-functional connector) • 1x USB Type-C 3.1: 10 Gbps • 2x USB Type-A 3.1: 10 Gbps • 1 x USB Type-A 2.0: 480 Mbps **Host Connector:** • USB Type-C 4.0: 40 Gbps with USB Power Delivery (PD 3.0) for fast charge of 100W (compatible with Thunderbolt 4)
Display Resolution[2]	**Hosts supporting Thunderbolt 4 /USB4 or MacBook M4, M4 Pro/Max[2]** Single Display: 8K (7680x4320@30Hz) or 4K (3840 x2160@144Hz) Dual Display: 8K (7680x4320@30Hz) + 4K (3840x2160@60Hz) or 4K (3840x2160@144Hz) + 4K (3840x2160@60Hz) **Hosts supporting MacBook M1 Pro/Max, M2 Pro/Max, M3 Pro/Max[2]** Single Display: 4K (3840x2160@144Hz) Dual Display: 4K (3840x2160@144Hz) + 4K (3840x2160@30Hz) **Hosts supporting MFDP with DP 1.4 or Thunderbolt 3 with DP 1.4[3]** Single Display: 4K (3840 x2160 Dual Display: Not Supported
Supported System	
Operating System	macOS, Windows 10, Windows 11, and Android
Physical	
Maximum Power Consumption (W)	Power adapter 149.1 W (21V/7.1A)
Dimensions	190 x 80 x 22 mm
Weight	332 g
Operating Temperature	0 to 40 °C
Storage Temperature	-20 to 65˚ C
Operating Humidity	10% to 90% non-condensing
Storage Humidity	5% to 95% non-condensing
Certifications	FCC CE
Package Contents	
DUF-901	9-in-1 USB4 Docking Station USB Type-C cable (50 cm) AC Adapter Quick Installation Guide Warranty Card

1. Backward compatible with previous USB versions.
2. Resolutions based on the input signal of the connected host computer (Please refer to your device 's specifications to identify display capability.) For MacBook M1, M2, and M3, only single display configuration with maximum resolution of 4K (3840 x2160@144Hz) is supported.
3. For a host computer using a MFDP (Multi-Function DisplayPort) with DP 1.2 or Thunderbolt 3 with DP 1.2, only single display configuration with maximum resolution of 4K (3840 x2160@30Hz) is supported.
4. References to power capability, signal or processing speed, signal range or distance, data encryption, storage capacity, display properties, or other performance metrics are based on optimal conditions derived from industry standards and provided for informational purposes only.

D-Link (Deutschland) GmbH, Schwalbacher Strasse 74, 65760 Eschborn, Germany
D-Link (Europe) Ltd, 3rd Floor, 166 College Road, Harrow HA1 1BH, United Kingdom

Specifications are subject to change without notice. ©2025 D-Link. All Rights Reserved. D-Link and the D-Link logo are trademarks or registered trademarks of D-Link. All other third-party marks mentioned herein may be trademarks of their respective owners.
v1.00 EU